1 YEAR WARRANTY

This Power Adapter is a perfect solution for small applications. High quality well-regulated adapter capable for powering up to 48 watt of MaxBrite Ribbon Strip and Cove Light, under cabinet lighting, etc.

Two Prong, Wall Mount Plug

Short circuit, overload, over voltage & over temperature protections

UL Listed U.S. and Canada

For indoor use only

Fully Isolated Plastic Case

Applications

- Cove Lightings
- Kitchen Cabinet Lighting
- LED indoor lightings
- Decorate lightings

60W Single Output Indoor Rated Constant Voltage LED Power Adapter



★ Specification

Input Voltage	100-240V AC full range (1.20A/100V 0.50A/240V)
Frequency	50Hz to 60Hz
Output Voltage	12V DC
Output Power	60W max
Output Current	5A (full load)
Efficiency	85%
Withstand Voltage	1000V AC 5 mA
Leakage Current	0.25mA/240v AC
Ripple and Noise	120mVp-p
Inrush Current	25°c Cold Start 30A/115v AC, 60A/230v AC

★ Environmental

Operating Temperatur	re -5°c to +40°c
Storage Temperature	-5°c to +60°c
Humidity	30%-90% (RH-NonCondensing)
Cooling	Air Convection
Vibration Frequency	10 to 500 Hz
MTBF	732Khrs min MIL-HDBK-217F(25°C)
Dimensions	4-1/2" x 2" x 1-3/16" (L x W x H)
Weight	4.00 oz.
Input Connection	Two Prong Wall Plug
Output Connection	Male Barrel 5.5X2.1 AWM 2725 30V, 80°c









★ Mechanical



