

VT12030D-120

Offers two levels of lighting: 100% and 65%



FEATURES AND BENEFITS

- Exclusive Ventex GTO lead clamping system*
- Ten-foot power cord (3 Pin)
- Pull-chain on/off switch
- Line load regulated (30mA self-adjusting output regardless of load size or Input voltage fluctuations)
- High power factor (energy saving/ cost effective)
- Grounding connection via mounting foot
- UL 2161 listed
- Complies with CSA22.2, No. 107.1, No.13
- Open circuit, short circuit and ground fault protection

SPECIFICATIONS

Input Voltage	120VAC (+/-10%) 50/60 Hz
Input Current	1.25A rms max.
Power Factor	.93
Output Frequency	Variable
Output Voltage	0V-12,000V
Output Current	30mA (2 Level Dimming)
Operating Temperature	32°F to 104°F / 0°C to 40°C
Driving Distance** (Based on Standard 12mm tube. Deduct one foot from driving footages for each pair of electrodes.)	
Neon	5-35 ft (1.5-10.7 m)
Mercury	5-41ft (1.5-12.5 m)

*Shown with optional Ventex GTO Lead Kit Part # 85340 GTO-10 Kit (8FT)

**See Ventex Luminous Tube Footage Chart for more information.

DIMENSIONS

Length (A)	6.60 in	16.8 cm
Width (B)	3.15 in	8.0 cm
Height (C)	2.0 in	5.0 cm
Mounting (D)	6.0 in	15.2 cm
Mounting (E)	2.25 in	5.7 cm
Weight	32.0 oz	907 g
Power Cord	10.0 ft	3.0 m
GTO Leads	GTO Clamping System*	

*Exclusive: Ventex GTO Lead Clamping system allows for easy field installation of properly sized GTO. Requirements: minimum of 10kV rated; .252 in. OD +/- 0.01; 4.0 ft maximum length for each output lead. Please refer to complete instructions in manual in box. Ventex GTO Kit available: Part # 85340 GTO-10 Kit (8FT)

Exclusive: These units are protected by Ventex's patented protective circuitry to prevent false tripping due to capacitive current. Patent #5892646

