

VT1510-12 Formerly NPS-12D5

Use with Ventex AC Adapter **



FEATURES AND BENEFITS

- UL and cUL listed to UL 2161
- Small size and lightweight
- Low-voltage input
- Use with argon and neon
- Use standard gas pressure
- Constant burn

SPECIFICATIONS

Input Voltage	11 to 14VDC
Input Current	600A rms (80%) 900A rms max.
Output Voltage	0V-1,500V
Output Current	15mA
Operating Temperature	32°F to 104°F / 0°C to 40°C
Driving Distance* (Based on Standard 12mm tube. Deduct one foot from driving footages for each pair of electrodes.)	
Neon	2-5 ft (0.6-1.5 m)
Mercury	2-6 ft (0.6-1.8 m)

*See Ventex Luminous Tube Footage Chart for more information.

DIMENSIONS

Length (A)	2.20 in	5.6 cm
Width (B)	2.25 in	5.7 cm
Height (C)	1.10 in	2.8 cm
Mounting (D)	1.75 in	4.5 cm
Mounting (E)	1.15 in	2.9 cm
Weight	3.2 oz	91 g
Primary Leads	8.0 in	20.3 cm
GTO Leads	18.0 in	45.7 cm

Male connector to mate with wall adapter power supply. **Ventex AC Adapter is found on page 72 of this catalog.

