

## VT9060CL-277



### FEATURES AND BENEFITS


- UL 2161 listed
- Complies with CSA22.2, No 107.1 and No. 3
- Open circuit, short circuit and ground fault protection
- All models are self-adjusting
- Automatic overload shutdown feature
- High power factor
- Grounding foot and green wire
- 1/2" conduit fitting for primary wiring
- Integral sleeve GTO (length listed below)
- Utilizes standard fill pressures

### SPECIFICATIONS

Input Voltage	277 VAC (±10%) 50/60Hz
Input Current	0.75A rms max.
Power Factor	0.98 min.
Output Frequency	Variable
Output Voltage	0V-9,000V
Output Current	60mA
Operating Temperature	-30°F to 122°F / -34°C to 50°C
Driving Distance* (Based on Standard 12mm tube. Deduct one foot from driving footages for each pair of electrodes.)	
Neon	4-26 ft (1.2-7.9 m)
Mercury	4-31 ft (1.2-9.5 m)

\*See Ventex Luminous Tube Footage Chart for more information.

Length (A)	8.63 in	22.0 cm
Width (B)	3.50 in	8.9 cm
Height (C)	1.70 in	4.3 cm
Mounting (D)	8.13 in	20.7 cm
Mounting (E)	2.25 in	5.7 cm
Weight	52.0 oz	1,474 g
Primary Leads	36.0 in	91.4 cm
GTO Leads	32.0 in	81.3 cm



Exclusive: These units are protected by Ventex's patented protective circuitry to prevent false tripping due to capacitive current. Patent #5892646

