


The Metropolitan®

PLASTICADE®

- **Six Signs** per Frame -  **Messaging**
 - two 24" x 36" signs
 - two side signs
 - two sided top rider
- Wheels for easy movement
- Quick-Change™ Feature
 - change signs in seconds, slide in a sign
- Arched top design
 - invisible hinges
- Customizable nameplate
- "Stay Tabs" hold main signs securely in place
- Internally weight with dry sand
- Available in white and black

**QUICK
CHANGE™**



Patented slot design
- just slide in a sign



Nameplate can be
Customized with
Your Name and Logo



Wheels



OUTSIDE DIMENSIONS : 45.54"H X 26.72"W x 3.58"D

DIMENSIONS OF RECESSED AREA: 34.75"H x 24.25"W

WEIGHT: 24 lbs.

COLORS: White, Black, Custom Colors Available

6 SIGNS PER FRAME

Sand Ballasting Instructions




Sand Fill Holes

Each sign frame has two fill holes.

Remove plugs from fill holes and fill each hole with sand. After filling, shake the frame to evenly distribute the sand at the bottom. 5 lbs. of sand per hole for a total of 10 lbs. per sign frame is recommended.


Play sand is suggested for ease of filling.

Main Signs Insertion Instructions:




Stay Tabs


1. Slide 24" x 36" sign down through the tabs



2. ...until sign rests on ground




3. Push sign up into slot



4. Slide sign down into bottom slot

Main Signs

Holds Signs
24"W x 36"H
(up to 3/16" thick)



Top Rider Insertion Instructions:

Insert Top Rider Before Inserting Side Signs

Stand the frame on the ground, spreading open the sign faces only half way. Place the Sign Rider in the opening at the top between the sign faces. Now, move the sign faces apart until fully extended.

You may want to cut a hole in the rider to make the handle accessible.





Side Signs Insertion Instructions:

A cutting template is available at plasticade.com.

Holds signs up to 1/4" thick.

If using corrugated plastic sheet for side signs, cut so flutes run horizontal to ground.

4 mm corrugated plastic sheet is recommended.




Channels


1. Lay frame flat on the ground. Lift up the top sign face.



2. Slide first Side Sign into top and bottom channels on one side of frame.




3. Slide second Side Sign into top and bottom channels on other side of frame.



Holes

4. Insert Stabilizing Bar into hole on bottom and top. Lift up sign frame by the handle to stand upright.



Stabilizing Bar

Watch the
Instructional
Video on
plasticade.com

MADE IN THE USA
US PATENTS
7,337,569 & 7,748,151

PLASTICADE®

7707 Austin Avenue
Skokie, IL 60077
phone (800) 772-0355
fax (847) 966-8074
Plasticade.com



HDPE