

Q-SOLV CD 4406 REDUCER

MSDS Number: S0013

Revision Date: 4/21/2015

Page 1 of 5

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Quill Hair & Ferrule LTD 1 Greengate Park Rd. P.O. Box 23927 Columbia, SC 29224

Contact:	Deborah Millar
Phone:	1-803-788-4499
Fax:	1-803-736-4731
Email:	dmillar@paint-info.com
Web:	www.qhfonline.com

Product Name:	Q-SOLV CD 4406 REDUCER
Revision Date:	4/21/2015
MSDS Number:	S0013
Common Name:	Paint Reducer
Product Code:	QSOLVCD4406
Chemical Formula:	Complex Mixture
Product Use:	Paint Solvent


24 Hours Emergency Number 1-800-451-8346

2	HAZARDS IDENTIFICATION
Route of Entry:	Eyes; Ingestion; Inhalation; Skin
Target Organs:	Eyes; Skin; Respiratory system; Cental nervous system; Hematopoietic system; Blood; Kidneys; Liver; Lymphiod system
Inhalation:	Anesthetic, may cause repiratory irritation and cns depression. Can cause irritation and inflammation of the respiratory tract. Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact:	May cause irritation, tearing and redness.
Eye Contact:	May cause irritation.
Ingestion:	Aspiration hazard: Harmful or fatal if swallowed.

NFPA: HMIS III:



Health = 2, Fire = 3, Reactivity = 0H*2/F3/PH0



	PERSC	NAL P	RO	TEC	стіоі	N INDEX	{
А	88			G	8 8+	+ 🗯 + 😽	6
в	Ø8 + 🕊	ŧ		Н	G+	• 🗲 + 📲	+ 😿
С	ØN + 🛋	÷ + *			1 22	• 🖛 + 💥	6
D	🕅 + 🕊	+ -		J	ل ا	• 🗲 + 🕇	+ 🐝
Е	ØR + 🛋	† + 🗑		Κ	% +	• 🗲 + 1	`+ I ⊾
F	ØQ + 🕊	+ 🛉 +	8	Х	or S.O.	It your supervis P. for "SPECIAL" ng directions	
A Safety Glasses	Splash Goggles	C Face Shield & Eye Protection	p Glove	*	9	Synthetic	
t Dust Respirat	tor U Wapor Respirator	W Solut & Vapor Respirator	y Fut Fa Respir		Z Airline Hood or Mask	Additional Info	rmation



Q-SOLV CD 4406 REDUCER

SDS

MSDS Number: S0013

Revision Date: 4/21/2015 Page 2 of 5

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Classifications:

Physical, Flammable Liquids, 3 Health, Aspiration hazard, 1 Health, Acute toxicity, 5 Dermal Health, Specific target organ toxicity - Single exposure, 3

Health, Specific target organ toxicity - Repeated exposure, 2

GHS Phrases:

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H313 - May be harmful in contact with skin

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

GHS Precautionary Statements:

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P271 - Use only outdoors or in a well-ventilated area.

P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+312+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.

Continue rinsing.

P370+378 - In case of fire: Use dry sand, dry chemical, or alcohol resistant foam for extinction.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P332+313 - If skin irritation occurs: Get medical advice/attention.

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name		ACGIH TLV (PPM)	OSHA PEL (PPM)
1330-20-7	70%	Xylene (o-,m-,p)		100	100
100-41-4	30%	Ethyl benzene		100	100

FIRST AID MEASURES

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Promptly flush skin with water until all chemical is removed. Get medical attention if needed.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion:	Get prompt, qualified medical attention. Seek immediate medical attention.



Q-SOLV CD 4406 REDUCER

MSDS Number: S0013

Revision Date: 4/21/2015

Page 3 of 5

FIRE FIGHTING MEASURES

SDS

Flammability:	NFPA Class 1C flammable liquid
Flash Point:	81 DEGREES F
Autoignition Temp:	810 DEGREES F
LEL:	1.0%
UEL:	7.0%

Dry powder, water spray, dry chemical, carbon dioxide, alcohol foam. Do not use a solid stream of water since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use nonsparking tools and equipment. Absorb spill with inert material, then place in chemical waste container. Remove/Dispose of in a manner consistent with federal and local law. Do not use combustible materials, such as saw dust. Do not flush to sewer. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect attempting to stop leak and to flush spills away from exposures.

7	HANDLING AND STORAGE
Handling Precautions: Storage Requirements:	Protect against physical damage. Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing. Protect against physical damage. Outside or detached storage is preferred. Seperate from oxidizing materials. Containers should be bonded and grounded from transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Containers of the material may be hazardous
	when empty since they retain product residues (vapors,liquid); observe all warnings and precautions listed for the product.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION		
Engineering Controls: Personal Protective Equ	 N/A uip: HMIS PP, K Properly fitted air purifying or air-fed respirator, glove, suit, and boots. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. QHF 		

recommends the use of a fresh air supply respirator.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: **Physical State:** Spec Grav./Density: **Boiling Point:** Vapor Pressure: pH:

Colorless liquid Liquid .87 267 F 7 mmHg @ 20 C N/A

Odor: Solubility: Percent Volatile: Freezing/Melting Pt.: Flash Point:

Light Aromatic Negligible 100% N/A 81 F



Q-SOLV CD 4406 REDUCER

MSDS Number: S0013

Revision Date: 4/21/2015 Page 4 of

Evap. Rate:

Materials to Avoid:

Hazardous Polymerization:

.6

Vapor Density: VOC:

3.7 871 GRAMS/LITER 7.26 LBS/GL

STABILITY AND REACTIVITY

SDS

Stability: Conditions to Avoid:

Product is stable under normal conditions. Oxidation promoting conditions (Heat, Sunlight and Air). Strong Acids Hazardous Decomposition: Carbon dioxide, oxides of nitrogen, carbon monoxide Will not occur.

TOXICOLOGICAL INFORMATION

ACUTE TOXICITY				
Ingredient Name	Test	Results	Route	Species
Xylene	LD 50	4300 mg/kg	Oral	Rat
	LC 50	5000 ppm / four hours	Inhalation	Rat
	LD 50	>1700 mg/kg	Dermal	Rabbit
Ethyl benzene	LD 50	3500 mg/kg	Oral	Rat
	LC 50	64000 ppm / four hours	Inhalation	Rat
	LD 50	15800 mg/kg	Dermal	Rabbit

ECOLOGICAL INFORMATION

Enviromental Fate: When released into the soil, this material is not expected to evaporate significantly. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, When released that the air, this material is expected to have the half-life of less than one day.

DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

DOT: Paint Related Material, 3, UN1263, PG III



Q-SOLV CD 4406 REDUCER

MSDS Number: S0013

Revision Date: 4/21/2015 Page 5 of 5

IATA: Paint Related Material, 3, UN1263, PG III

MULTI-MODAL: Paint Related Material, 3, UN1263, PG III



REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Xylene (o-,m-,p- isomers) (1330-20-7 70%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TXAIR, TXHWL

*Ethyl benzene (100-41-4 30%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TXAIR

REGULATORY KEY DESCRIPTIONS

_____ CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EPCRAWPC = EPCRA Water Priority Chemicals HAP = Hazardous Air Pollutants MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = ŠARA 313 Title III Toxic Chemicals TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List) TXAIR = TX Air Contaminants with Health Effects Screening Level TXHWL = TX Hazardous Waste List PRIPOL = Clean Water Act Priority Pollutants TOXICPOL = Clean Water Act Toxic Pollutants

	OTHER INFORMATION
--	-------------------

Quill Hair & Ferrule LTD believes that the data contained herein is accurate and derived from qualified sources. The data is not to be taken as a warranty or representation for which Quill Hair & Ferrule LTD assumes legal responsibility. It is offered solely for your consideration, investigation, and verification. Any use of this data and information should be determined by the end user in accordance with Federal, State and local laws and regulations.