

SloanLED SE

Maximum efficiency, low cost solution

Specifications

Part number	701269-6WSK1-MB
Dimensions L × W × H	0.85 in × 0.45 in × 0.28 in (22 mm × 11 mm × 7 mm)
Viewing angle	120°
LEDs per module	1
Modules per foot/meter	2.5/8.2
Operating temperature	-40° C to +70° C
Binning	MacAdam Step 3
Power per module	0.43 W
Efficacy	108 lm/W
Power capacity	125 modules (50 ft/15.2 m) per SloanLED 60 W 12 VDC power supply
Fastening	Peel-n-stick
Packaging	20 ft/6.1 m (50 modules) per tray, 10 trays per carton
Color temperature	6500 K
Lumens per module	46



For photobiological compliance, the illuminance Ethr at RG1/RG2 border is 813 lux.

SloanLED channel letter products are covered by US and foreign patents pending and covered by one or more of the following US patents issued: 6,932,495, 7,160,140, 7,241,031, 7,520,771, 7,931,386 and European Patent No. 1756471.



Use the online SloanLED Layout Estimator to get a quick SloanLED SE design and material estimate for your sign.
Visit [product page](#) for details.

SloanLED Headquarters
805.676.3200 • info@SloanLED.com
SloanLED.com

SloanLED Europe b.v.
+31 88 12 44 900 • Europe@SloanLED.com

