

Sunea® RTS CMO (Compact Manual Override)

Specifically designed for use in cassette and standard retractable awnings only

525A2 CMO 1114230
535A2 CMO 1116266
550R2 CMO 1118167




Radio Technology Somfy (RTS) allows for wireless radio control of motorized window coverings via the RTS family of controls.

Technical Features

Voltage Supply	120V AC, 60Hz	Temperature Working Range	14°F to 104°F (-10°C to 40°C)
Index Protection Rating	IP 44	Insulation Class	Class 1 for 120V AC
Limit Switch Type	Electronic RTS	Antenna	Integrated into power cord. Must be at least 12 inches and must not come in contact with metal.
Limit Switch Capacity	250 Turns	Wiring	Parallel wiring allowed in accordance with NEC and local electrical codes.

Dimensions



Dimensions	525A2 CMO	535A2 CMO	550R2 CMO
L1	27.40 in. (696 mm)	27.40 in. (696 mm)	27.40 in. (696 mm)
L2	26.93 in. (684 mm)	26.93 in. (684 mm)	26.93 in. (684 mm)
L3	28.35 in. (720 mm)	28.35 in. (720 mm)	28.35 in. (720 mm)

Optional fast connector cables with NEMA plugs available in 11 ft, 17 ft, 23 ft.

Specifications

	525A2 CMO	535A2 CMO	550R2 CMO
Torque	25 Nm	35 Nm	50 Nm
Nominal Voltage	120V / 60HZ		
Rated Current	1.6A	2.1A	2.1A
Speed	20 rpm	20 rpm	14 rpm
Thermal Protection	4 minutes		
Radio Frequency	433.42 MHz		

Type of power cable - SJTW + 18 in.

Fast Connector - Male
 (Do not cut fast connector cable)

