

DATA SHEET

DIGIJET 909 METROMARK™

3.5 MIL MATTE WHITE OPAQUE TRANSIT VINYL CLEAR REMOVABLE ADHESIVE

DigiJet 909 Metromark™ is a 3.5 mil matte white polymeric flexible opaque vinyl film coated with a removable acrylic pressure-sensitive adhesive on a 90# layflat liner printed with the Metromark™ logo. This film is designed to accept latex, solvent-based inkjet and UV curable inks common to wide format digital printing systems, and can be sheeted for screen printing. DigiJet 909 is designed for temporary applications including product markings, point of purchase decals, transportation advertising systems, and tri-vision indoor/outdoor billboard displays. DigiJet 909 will conform to simple curves and has excellent hiding characteristics for multi-layered graphics. The adhesive formulation allows for install on glass and OEM painted metal with a surface temperature of 20°F.

PRODUCT NAME	909	
FILM		
Film Type	White Polymeric Vinyl	
Film Thickness (mils / µm)	3.5 / 89 (+/- 10%)	
Film Weight (gsm)	130	
Gloss (60°)	≤20	
Opacity (%)	99	
Tensile Strength (psi)	MD ≥ 3500 / CD ≥ 2500	
Elongation (%)	$MD \ge 90 / CD \ge 200$	
Dimensional Stability (FTM 14)	MD ≤ 0.30 mm / CD ≤ 0.20 mm	
ADHESIVE		
Adhesive Type	Emulsion	
Adhesive Thickness (mils/µm)	0.8-1.0 / 20-25	
Adhesive Color	Clear	
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	1.5 / 6.6	
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	2.3 / 10	
LINER		
Liner Weight (#/gsm)	90 / 145	
Liner Type	White 2-Sided PE Coated Kraft, backside logo liner	
Liner Thickness (mils/µm)	6.7 / 170	
Release Force @ 300" / min (g/2")	40-70	
PERFORMANCE GUIDANCE		
Application Temperature	≥ +20 °F	
Service Temperature	-40 °F to 180 °F	
Shelf Life	6 months	
Storage Temp / Rel. Humidity	70 °F / 50%	
Outdoor Durability	up to 5 years	
Removability	1 year	



TECHNICAL DATA SHEET

DIGIJET 909 - 3.5 MIL MATTE WHITE TRANSIT VINYL CLEAR REMOVABLE ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
APPLICATION	• POP/RETAIL	• SOLVENT
O WET APPLY	• WALL	• ECO-SOLVENT
• DRY APPLY	• WRAP	• LATEX
O LAMINATING	• WINDOW	• UV CURABLE
O MOUNTING	O FLOOR	• SCREEN
• DIE CUTTABLE	O TRANSLUCENT	• OFFSET (UV CURABLE)
O HOT STAMP	• TRANSIT	• OFFSET (CONVENTIONAL)*
O THERMAL DIE	• GENERAL SIGNAGE	
• FLATBED CUTTABLE	• OUTDOOR (LONG TERM)	
SUBSTRATES		
• OEM PAINTED METAL		
PAINTED ALUMINUM		
• STAINLESS STEEL		
• FIBERGLASS		* Topcoated verstion is available for conventional offset printing.

FAQS	
Is DigiJet 909 MetroMark™ Transit Approved?	Yes. MetroMark [™] is an approved and specified material for multiple transit-related applications including King/Queen/Tail bus advertisements, opaque removable graphics, and layered poster graphics.
Can DigiJet 909 be used as a wrap film?	MetroMark™ is conformable film that can go around simple curved surfaces. The adhesive system is strong enough to hold your graphic in place, but robust enough to remove cleanly.
Can you put DigiJet 909 over the top of existing graphics?	Yes. DigiJet 909 is opaque and can be layered on top of existing graphics. These films can be used for one, two and three sheet subway advertising posters, architectural signage, commercial-retail signage, industrial identification decals, safety decals, point-of-purchase graphics and other decals requiring extended life. Keep in mind, adhesive vinyl products can bond with other vinyl materials and might not allow MetroMark™ to be removed cleanly from other graphics.
Should MetroMark™ be laminated?	Although it is not necessary to laminate MetroMark™, you may choose to do so depending upon what type of abrasion and or cleaning detergents the graphics will encounter. DigiJet 900 series overlaminates are recommended in those situations.